EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST W. T. RYAN #1100 AGENCY GOODYEAR POLICE DEPT			
DATE 1-21-15 TIME 1029			
INTOXILYZER SERIAL # 80-001858 LOCATION [11] S LITCHFIED B GOUDYGAN			
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution O. 100AC.			
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C			
2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START" 3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.			
4. Air blank completed. 5. Calibration check completed. Test results 0 () 9 9			
6. Air blank completed. 7. Remove printed record. Attach the record to the completed checklist.			
SIGNATURE W.T. Regan 1100			
DPS Form Exh G-2 (Rev 05-01)			

NO PROBLEMS NOTED

INTOXILYZER 8000

Location: 1111 S LITCHFIELD RD

Serial Number: 80-001858 Core Version: 8105.48

01/21/2015 10:29:05

Standard Lot#: 25913100A2

Last Changed By: W. RYAN #1100

QAS: W. RYAN #1100

GOODYEAR PD

Operator: W. RYAN #1100

GOODYEAR PD

Test g/210L Time

	9/2100	TIME
	·	
Air Blank	0.000	10:30:33
0.100 Cal Check	0.099	10:30:54
Air Blank	0.000	10:31:24

Preventative Maintenance Performed -- Timer Reset