EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST W. T. RYAN #1100 AGENCY GOODYEAR POLICE DEDT
DATE 3-16-15 TIME 1920
INTOXILYZER SERIAL # 80-000312 LOCATION []] S LITCHFLED PO GODYGAZ AZ
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution O. 100 AC.
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
 Intoxilyzer 8000 display reads "PUSH BUTTON TO START" Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
4. Air blank completed. 5. Calibration check completed. Test results 0 100 AC
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE W. T. Ruger 1100
DPS Form Exh G-2 (Rev 05-01)

INTOXILYZER 8000

Location: 1111 S LITCHFIELD RD

Serial Number: 80-000312 Core Version: 8105.48

03/16/2015 19:20:01

Standard Lot#: 25913100A2 Last Changed By: W. RYAN #1100

QAS: W. RYAN #1100

GOODYEAR PD

Operator: W. RYAN #1100

GOODYEAR PD

Test	g/210L	Time
Air Blank	0.000	19:22:23
0.100 Cal Check	0.100	19:22:44
Air Blank	0.000	19:23:14

Preventative Maintenance Performed -- Timer Reset