EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST W. T. RYAN # 1100 AGENCY GOODY FOR POLICE) EPT
DATE 7-22-15 TIME 1041	
INTOXILYZER SERIAL # 80-0003/2 LOCATION [1] S LITCHFIGLO 1	S Good
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution OR	<u>, 100</u> ac.
Pour a standard alcohol concentration solution AC, into a clean dry simulator and assemb simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reac 0.2°C	
 Intoxilyzer 8000 display reads "PUSH BUTTON TO START" Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After so made press ENTER. 	election is
4. Air blank completed. 5. Calibration check completed. Test results 0. 102 AC. 6. Air blank completed.	
7. Remove printed record. Attach the record to the completed checklist.	
SIGNATURE W.T. Ruga 1100	
DPS Form Exh G-2 (Rev 05-01)	

NO PROBLEMS

INTOXILYZER 8000

Location: 1111 S LITCHFIELD RD

Serial Number: 80-000312 Core Version: 8105.48

07/22/2015 10:41:08

Standard Lot#: 26614100A6
Last Changed By: W. RYAN #1100

QAS: W. RYAN #1100

GOODYEAR PD .

Operator: W. RYAN #1100

GOODYEAR PD-

Test	g/210L	Time
Air Blank	0.000	10:46:18
0.100 Cal Check	0.102	10:46:39
Air Blank	0.000	10:47:09

Preventative Maintenance Performed -- Timer Reset