## EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

## ARIZONA DEPARTMENT OF PUBLIC SAFETY

## STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

## STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST W. T. RYAN #1100 AGENCY GODDYON POLICE DEP
DATE 4-5-18 TIME 1723
INTOXILYZER SERIAL # 80-001858 LOCATION II N 145TH AVE GOODY CAR AZ
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution AC.
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
<ol> <li>Intoxilyzer 8000 display reads "PUSH BUTTON TO START"</li> <li>Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.</li> </ol>
4. Air blank completed. 5. Calibration check completed. Test results 0 000
6. Air blank completed. 7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE W.T. Regan 1100
DPS Form Exh G-2 (Rev 05-01)

INTOXILYZER 8000

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

04/05/2018 17:23:09

......

Standard Lot#: 23016100A1

Last Changed By: M. GUILBAULT #1144

-----

QAS: W. RYAN #1100

GOODYEAR PD

------

Operator: W. RYAN #1100

GOODYEAR PD

-----

Test	g/210L	Time
Air Blank	0.000	17:23:41
0.100 Cal Check	0.099	17:24:02
Air Blank	0.000	17:24:32

Preventative Maintenance Performed -- Timer Reset