INTOXILYZER 8000

Location: 11 N 145TH AVE Serial Number: 80-000312 Core Version: 8105.48

05/05/2018

17:13:57

Standard Lot#: 14816100A1 Last Changed By: W. RYAN #1100

QAS: W. RYAN #1100

GOODYEAR PD

Operator: W. RYAN #1100

GOODYEAR PD

Test	g/210L	Time
Air Blank	0.000	17:14:36
0.100 Cal Check	0.096	17:14:57
Air Blank	0.000	17:15:27

Preventative Maintenance Performed -- Timer Reset

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST W. T. RYAN #1/00 AGENCY GOODYON POLICE DEPT
DATE 5-5-18 TIME 1713 HRS
INTOXILYZER SERIAL # 30-000312 LOCATION 11 N 14574 AUG, GOODYON AZ
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution OR
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START" 3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
4. Air blank completed. 5. Calibration check completed. Test results 0. O96 AC. 6. Air blank completed. 7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE W. T. Pager 1100
DPS Form Exh G-2 (Rev 05-01)

NO PRUBLENS