EXHIBIT 2

THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R9-14-404(A)

ARIZONA DEPARTMENT OF HEALTH SERVICES

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

AGENCY (500 DYEAR POLICE DEPARMENT		
DATE Z	8 200F TIME 14:47		
INTOXILYZER SERIAL NO. 80-000312 LOCATION GOODY OR PD			
QA SPECIALIS			
	(print name)		
(U) 1.	Ensure dry gas tank is attached to instrument and contains a known alcohol		
(-) 1.	standard (00 AC.		
	OR		
	Pour a standard alcohol solution of known value,AC, into a clean		
	dry simulator and assemble the simulator. Ensure that a tight seal has been		
	made. Turn on the simulator and allow temperature to reach 34°C ± 0.2 °C		
(L) 2.	Intoxilyzer 8000 display reads "PUSH BUTTON TO START"		
(4) 3.	Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.		
(h) 4.	Air blank completed.		
-(k) 5.	Calibration check completed. Test results 0. 098 AC.		
(U) 6.	Air blank completed.		
(4) 7.	Remove printed record. Attach the record to the completed checklist.		
SIGNATURE:_	\mathcal{S}		

Location: GOODYEAR POLICE DEPT

Serial Number: 80-000312

02/18/2005 14:47:51

Standard Lot#: 422601G

Last Changed By: W. WILL #974

QAS: W. WILL #974

GOODYEAR PD

Test	g/210L	Time
Air Blank	0.000	14:48:18
Cal Check	0.098	14:48:37
Air Blank	0.000	14:49:06

Operator's Signature

EXHIBIT 3

THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R9-14-404(A)

ARIZONA DEPARTMENT OF HEALTH SERVICES

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD QUALITY ASSURANCE PROCEDURE

AGENCY (GOODYEAR POLICE DEPARTMENT
DATE Z	(18/2005 TIME (447)
INTOXILYZ	er serial no. 80 -000 312 Location Goody R
	LIST Wice
	(Print Name)
(W1.	Display Reads "PUSH BUTTON TO START"
DIAGNOSTI	C TESTS -
	Clock time check.
	Date cheek.
OPERATION	
(U) 1.	
(L) 2.	Error recognition logic system functioning.
A) 3.	Not a Successfully Completed Test Sequence printed Proper sample recognition system.
(4) 3.	Not a Successfully Completed Test Sequence printed
	Deficient sample printed.
(V) 4.	Calibration standard 0. 100 AC. Result 0. 098 AC.
Instrument is	operating properly and accurately. YES NO
	-
COMMENTS	S:
	A
SIGNATURE	

Location: GOODYEAR POLICE DEPT

Serial Number: 80-000312

02/18/2005

14:49:35

Standard Lot#: 422601G Last Changed By: W. WILL	#974
QAS: W. WILL GOODYEAR PD	#974
Operator: W. WILL GOODYEAR PD	#974

Subject: TEST, TEST DOB: 11/11/1111

Sex: M

Weight: 1

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	14:50:27
Diagnostic Test	Pass	14:50:54
Air Blank	0.000	14:51:21
0.100 Cal Check	0.099	14:51:40
Air Blank	0.000	14:52:09
Subject Test	0.000	14:52:29
Air Blank	0.000	14:52:56
Five Minute Wait	ABT*	
Air Blank	0.000	14:53:31

^{*}Sequence Aborted

Location: GOODYEAR POLICE DEPT

Serial Number: 80-000312

02/18/2005

14:53:36

Standard Lot#: 422601G Last Changed By: W. WILL	#974
QAS: W. WILL GOODYEAR PD	#974
Operator: W. WILL GOODYEAR PD	#974

Subject: TEST, TEST DOB: 11/11/1111

Sex: M

Weight: 1

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	IPS*	14:54:33
Air Blank	0.000	14:55:01

^{*}Improper Sample

Location: GOODYEAR POLICE DEPT

Serial Number: 80-000312

02/18/2005

14:55:06

Standard Lot#: 422601G Last Changed By: W. WILL	#974
QAS: W. WILL GOODYEAR PD	#974
Operator: W. WILL GOODYEAR PD	#974

Subject: TEST, TEST DOB: 11/11/1111

Sex: M

Weight: 1

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	RFI*	14:55:35
Air Blank	0.000	14:56:03

^{*}RFI Detect

Location: GOODYEAR POLICE DEPT

Serial Number: 80-000312

02/18/2005 14:56:08

Standard Lot#: 422601G
Last Changed By: W. WILL #974

QAS: W. WILL #974

GOODYEAR PD

Operator: W. WILL #974

GOODYEAR PD

Subject: TEST, TEST DOB: 11/11/1111

Sex: M Weight: 1

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	14:56:57
Diagnostic Test	Pass	14:57:25
Air Blank	0.000	14:57:52
0.100 Cal Check	0.098	14:58:11
Air Blank	0.000	14:58:40
Subject Test	0.302*	15:01:49
Air Blank	0.000	15:02:21
Air Blank	0.000	15:02:48
Subject Test	XXX**	15:03:08
Air Blank	0.000	15:03:40

^{*}Deficient Sample

Begin new deprivation period

^{**}Invalid Sample

EXHIBIT 2

THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R9-14-404(A)

ARIZONA DEPARTMENT OF HEALTH SERVICES

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

AGENCY (JOUDYEAR POLICE DEPARMENT
DATE Z(18	,
INTOXILYZER	R SERIAL NO. 80-000312 LOCATION GOODYSAR PD
QA SPECIALIS	
	(print name)
(U) 1.	Ensure dry gas tank is attached to instrument and contains a known alcohol standard/00AC.
	OR Pour a standard alcohol solution of known value,AC, into a clean
	dry simulator and assemble the simulator. Ensure that a tight seal has been
	made. Turn on the simulator and allow temperature to reach 34°C ± 0.2 °C
(p) 2.	Intoxilyzer 8000 display reads "PUSH BUTTON TO START"
(4) 3.	Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
(W 4.	Air blank completed.
()-5.	Calibration check completed. Test results 0. 098 AC.
W 6.	Air blank completed.
(1) 7.	Remove printed record. Attach the record to the completed checklist.
SIGNATURE:	

Location: GOODYEAR POLICE DEPT

Serial Number: 80-000312

02/18/2005

15:03:59

Standard Lot#: 422601G

Last Changed By: W. WILL #974

QAS: W. WILL #974

GOODYEAR PD

Test		g/210L	Time
Air	Blank	0.000	15:04:26
Cal	Check	0.098	15:04:45
Air	Blank	0.000	15:05:15

Operator's Signature