EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST W. T. RYAN 1100 AGENCY GOODYEAR POUCE DEP	
DATE 2-1-2019 TIME 1444 HRS	
INTOXILYZER SERIAL # 90 - 00/858 LOCATION // N/45TH AVE GOUDYOU AZ 6533	8
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution OR	
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C	
 Intoxilyzer 8000 display reads "PUSH BUTTON TO START" Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER. 	
4. Air blank completed. 5. Calibration check completed. Test results 0. /DO AC. 6. Air blank completed.	
7. Remove printed record. Attach the record to the completed checklist	
SIGNATURE W. T. Rya 1100	
DPS Form Exh G-2 (Rev 05-01)	

INTOXILYZER 8000

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

02/01/2019 14:44:38

Standard Lot#: 10818100A1 Last Changed By: W. RYAN #1100

QAS: w. ryan #1100

goodyear pd

Operator: w. ryan #1100

goodyear pd

Test	g/210L	Time
Air Blank	0.000	14:45:11
0.100 Cal Check	0.100	14:45:32
Air Blank	0.000	14:46:02

Preventative Maintenance Performed -- Timer Reset