EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST W. T. RYD +1100 AGENCY GOODYGOR POUCH DOS
DATE 3-2-2019 TIME 1644 HPS
INTOXILYZER SERIAL # 90 - 00 (858 LOCATION 1/1 N 14574 ALE, G-OOD YOR AZ 65338
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution 0, 100 AC.
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START" 3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet and all the start of the start o
(VF 4. Air blank completed.
5. Calibration check completed. Test results 0. 100 AC. 6. Air blank completed. 7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE W. T. Rever # 1/00
OPS Form Exh G-2 (Rev 05-01)

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

03/02/2019 16:44:57

Standard Lot#: 10818100A1 Last Changed By: W. RYAN #1100

QAS: w. ryan #1100

goodyear pd

Operator: w. ryan #1100

goodyear pd

Test	g/210L	Time
Air Blank	0.000	16:45:29
0.100 Cal Check	0.100	16:45:50
Air Blank	0.000	16:46:20

EXHIBIT G-4 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST W. T. RYAN # 1100 AGENCY GOODYOR POCKE DEF
DATE_3-2-2019 TIME 1647 HRS
INTOXILYZER SERIAL # 90 - 001858 LOCATION 11 N 145774 W.K., G-0004692
(1. Display Reads "PUSH BUTTON TO START"
DIAGNOSTIC TESTS () 1. Clock time check. () 2. Date check.
OPERATIONAL TESTS () 1. Alcohol-free subject test result 0. O 0 6 AC. 2. Error recognition logic system functioning. Not a Successfully Completed Test Sequence printed 3. Proper sample recognition system. Not a Successfully Completed Test Sequence printed Deficient sample printed. 4. Standard Calibration Check standard 0. O AC. Result 0. O AC. Instrument is operating properly and accurately. YES NO NO
COMMENTS
IGNATURE W. T. Rugan # 1100
PS Form Evh G-4 (Rev 05-01)

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

03/02/2019

16:47:59

Standard Lot#: 10818100A1 Last Changed By: W. RYAN	#1100
QAS: w. ryan goodyear pd	#1100
Operator: w. ryan goodyear pd	#1100

Subject: TEST, TEST DOB: 03/02/1959

Sex: M

Weight: 180

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	16:49:03
Diagnostic Test	Pass	16:49:38
Air Blank	0.000	16:50:05
0.100 Cal Check	0.100	16:50:26
Air Blank	0.000	16:50:57
Subject Test	0.000	16:51:11
Air Blank	0.000	16:51:38
Wait	ABT*	
Air Blank	0.000	16:52:28

^{*}Sequence Aborted

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

03/02/2019

16:52:46

Standard Lot#: 10818100A1

Last Changed By: W. RYAN #1100

QAS: w. ryan #1100

goodyear pd

Operator: w. ryan #1100

goodyear pd

Subject: TEST, TEST

DOB: 03/02/1959

Sex: M Weight: 180

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	IPS*	16:53:24
Air Blank	0.000	16:53:52

^{*}Improper Sample

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

03/02/2019 16:54:38

Standard Lot#: 10818100A1

Last Changed By: W. RYAN #1100

QAS: w. ryan #1100

goodyear pd

Operator: w. ryan #1100

goodyear pd

Subject: TEST, TEST DOB: 03/02/1959

Sex: M Weight: 180

15 Minute Deprivation Period? Yes

 Test
 g/210L
 Time

 Air Blank
 RFI*
 16:55:15

 Air Blank
 0.000
 16:55:43

^{*}RFI Detect

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

03/02/2019 16:56:37

Standard Lot#: 10818100A1
Last Changed By: W. RYAN #1100

QAS: w. ryan #1100
goodyear pd

Operator: w. ryan #1100
goodyear pd

Subject: TEST, TEST DOB: 03/02/1959

Sex: M Weight: 180

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	16:57:33
Diagnostic Test	Pass	16:58:08
Air Blank	0.000	16:58:36
0.100 Cal Check	0.100	16:58:57
Air Blank	0.000	16:59:27
Subject Test	0.295*	17:02:34
Air Blank	0.000	17:03:08
Air Blank	0.000	17:03:35
Subject Test	XXX**	17:04:01
Air Blank	0.000	17:04:36

^{*}Deficient Sample

Begin new deprivation period

^{**}Invalid Sample

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

03/02/2019 17:05:37

Standard Lot#: 10818100A1

Last Changed By: W. RYAN #1100

QAS: w. ryan #1100

goodyear pd

Operator: w. ryan #1100

goodyear pd

Test	g/210L	Time
Air Blank	0.000	17:06:07
0.100 Cal Check	0.098	17:06:27
Air Blank	0.000	17:06:58

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QASPECIALIST N. Gu. Bault	AGENCY	680
DATE3/29/19	TIME	1715
INTOXILYZER SERIAL# 80-00/818	LOCATION	6PA
1. Ensure that gas tank is attached to instrument and	contains a standard	alcohol concentration solutionAC
Pour a standard alcohol concentration solution simulator. Ensure that a tight seal has been made. 0.2°C	AC into	a clean dry simulator and assemble the tor and allow temperature to reach 34°C ±
 2. Intoxilyzer 8000 display reads "PUSH BUTTON T 3. Go to the "Control Testing Menu". Select "D" for made press ENTER. 	O START" dry control test or "	W" for wet control test. After selection is
4. Air blank completed. 5. Calibration check completed. Test results 0. / 0 6. Air blank completed.		*
7. Remove printed record. Attach the record to the con	mpleted checklist.	
SIGNATURE 70 1/4 4	·	
DDC F F 1 C 2 C		

DPS Form Exh G-2 (Rev 05-01)

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

03/29/2019

(12:15:10) P _____ Standard Lot#: 10818100A1 Last Changed By: W. RYAN #1100

QAS: m. guilbault #1144

goodyear pd

Operator: m. guilbault #1144

goodyear pd

Test	g/210L	Time
Air Blank	0.000	12:15:40
0.100 Cal C	heck 0.101)	12:16:01
Air Blank	0.000	12:16:31



CANister Charge MG 3/29/19

7 Eastgate Dr. • P.O. Box 790 • Jacksonville, IL 62651-0790 217-245-2183 • Fax: 217-243-7634 • www.ilmoproducts.com

Certificate of Analysis

Certificate ID:

11089

Part #:

BAC105L100T

Cylinder Size:

105L

Lot Number:

10818100A1

Expiration:

6/5/2020

0.100 BAC (For the calibration of instruments used to determine breath alcohol concentration)

Contents:

105 Liters @ 1000 psig 70°F (21°C)

Analytical

Reported

Accuracy

Analytical

Component:

Concentration:

(U, k=2):

Method:

Ethanol Nitrogen

260 ppm Balance +/-0.002 BAC(G/210L) NDIR

[5.2 ppm]

Distributed by:

CMI Inc.

316 East Ninth Street Owensboro, KY 42303 Phone 866-835-0690

www.alcoholtest.com

*NIST Traceable Reference Material Cylinder No. CC274523 / Job No. 09160306 Certified 362.2 µmol/mol Ethanol in Nitrogen

Store in dry area, away from sources of heat, ignition and direct sunlight. Do not allow storage area to exceed 52 °C (125 °F).

Specialty Gas Lab Tech

The calibration results within this certificate were obtained using equipment and standards capable of producing analytical results traceable to NIST, and apply only to the items contained on this certificate. ILMO Products Company makes no warranty or representation as to the suitability of the use of any information provided for any particular purpose. The information use is at the sole discretion and risk of the user. Liability shall be limited to established replacement cost of this material or service.

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. GUIL GAULT	AGENCY	GOOTY EAR PO
DATE 3/29/19	· TIME	1217
INTOXILYZER SERIAL # 80-06/858	_LOCATION_	690
1. Ensure that gas tank is attached to instrument and	l contains a standa	ard alcohol concentration solution / POAC
Pour a standard alcohol concentration solution simulator. Ensure that a tight seal has been made 0.2°C	AC, in . Turn on the sim	nto a clean dry simulator and assemble the nulator and allow temperature to reach 34°C \pm
 Intoxilyzer 8000 display reads "PUSH BUTTON Go to the "Control Testing Menu". Select "D" fo 	TO START" r dry control test o	or "W" for wet control test. After selection is
made press ENTER. 4. Air blank completed. 5. Calibration check completed. Test results 0.		
6. Air blank completed. 7. Remove printed record. Attach the record to the complete conductions of the conduction of the		st.
IGNATURE 1144	9	
*		

DPS Form Exh G-2 (Rev 05-01)

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

03/29/2019

Standard Lot#: 10818100A1

Last Changed By: m. guilbault #1144

.____

QAS: m. guilbault #1144

goodyear pd

Operator: m. guilbault #1144

goodyear pd

Test	g/210L	Time
Air Blank	0,000	12:18:16
0.100 Cal Check	0.101	12:18:37
Air Blank	(0.000	12:19:08