EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. GUELBAUT AGENCY GOOD GERN PA
DATE 9/9/09 TIME 1875
INTOXILYZER SERIAL # 8000 3/8 LOCATION GOOS 4 EAR \$2
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution AC.
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C 2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START" 3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is
made press ENTER. 4. Air blank completed. 5. Calibration check completed. Test results 0. AC. 6. Air blank completed. 7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE 144
DPS Form Evh G-2 (Rev 05-01)

INTOXILYZER 8000 Location: GOODYEAR PD Serial Number: 80-000312 09/09/2009 10:34:43 -----Standard Lot#: 562576 Last Changed By: M. GUILBAULT #1144 QAS: M. GUILBAULT #1144 GOODYEAR PD Test g/210L 10:35:10 Air Blank Cal Check 10:35:29 Air Blank

Operator's Signature

EXHIBIT G-4 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST M. GURLMANUT AGENCY GOODYEAR PO
DATE 9/9/09 TIME 1837 INTOXILYZER SERIAL # 80-00317 LOCATION GOOD 4 EAR 10 # 2
INTOXILYZER SERIAL # 80-00317 LOCATION GOOD 4 EAR D # 3
1. Display Reads "PUSH BUTTON TO START"
DIAGNOSTIC TESTS () 1. Clock time check. () 2. Date check.
OPERATIONAL TESTS 1. Alcohol-free subject test result 0. OO AC. 2. Error recognition logic system functioning. Not a Successfully Completed Test Sequence printed 3. Proper sample recognition system. Not a Successfully Completed Test Sequence printed Deficient sample printed. 4. Standard Calibration Check standard 0. OO AC. Result 0. OO AC.
Instrument is operating properly and accurately. YES NO
COMMENTS
SIGNATURE MALLEY
DPS Form Exh G-4 (Rev 05-01)

INTOXILYZER 8000

Location: GOODYEAR PD

Serial Number: 80-000312

09/09/2009

10:36:29

Standard Lot#: 562 Last Changed By: M		#1144
QAS: M. GUILBAULT GOODYEAR PD	·	#1144
Operator: M. GUILBAULT GOODYEAR PD		#1144
Subject: SQAP, TEST DOB: 01/01/2000 Sex: M	Weight: 100	

15 Minute Deprivation Period? Yes

Test	~/2101	- ·
	g/210L	Time
Air Blank	0.000	10:37:49
Diagnostic Test	Pass	10:38:16
Air Blank	0.000	10:38:44
0.100 Cal Check	0.102	10:39:02
Air Blank	0.000	10:39:32
Subject Test (0.000	(10:39:49)
Air Blank	0.000	10:40:16
Five Minute Wait	ABT*	
Air Blank	0.000	10:40:52

^{*}Sequence Aborted

INTOXILYZER 8030
Location: GOODYERR PD
Serial Number: 80-000312
59/05/2009 10:41:25
Standard Lot#: 562576
Last Changed By: M. GUILBAULT #1144
OAS: M. GUILBAULT #1144
GOCDYEAR PD
Operator: M. GUILBAULT #1144
GOODYEAR PD
Subject: SOAP, TEST
DOB: 01/01/2000
Sex: M. Weight: 100
15 Minute Deprivation Period? Yes

Test g/210t Time

Air Blank iPS*
Air Blank RFI**

*Improper Sample **RFI Detect

Not a Successfully Completed Test Sequence INTOXILYZER 8000

Location: GOODYEAR PD

Serial Number: 80-000312

09/09/2009

10:42:47

	10.42:4/
Standard Lot#: 562576 Last Changed By: M. GUILBAULT	#1144
QAS: M. GUILBAULT GOODYEAR PD	#1144
Operator: M. GUILBAULT GOODYEAR PD	#1144
Subject: SQAP,TEST DOB: 01/01/2000 Sex: M Weight: 100	

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	······································
Diagnostic Test	Pass	10:43:47
Air Blank	0.000	10:44:16
0.100 Cal Check	0.102	10:44:43
Air Blank	0.102	10:45:02
Subject Test	(0.064)	10:45:31
Air Blank	0.000	10:48:40
Air Blank	0.000	10:49:14
Subject Test	(XXX**)	(10:49:41)
Air Blank	AAA	10:50:17
	0.000	10:50:51

^{*}Deficient Sample

Begin new deprivation period

^{**}Invalid Sample

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. GUCLBAULT AGENCY GOODYEAR PO
DATE 9/9/09 TIME 1052
INTOXILYZER SERIAL # 80-800312 LOCATION GOODYEAR PORT
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
 Intoxilyzer 8000 display reads "PUSH BUTTON TO START" Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
4. Air blank completed. 5. Calibration check completed. Test results 0. AC. 6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE 1144
DPS Form Exh G-2 (Rev 05-01)

INTOXILYZER 8000 Location: GOODYEAR PD Serial Number: 80-000312 09/09/2009 10:51:34 Standard Lot#: 562576 Last Changed By: M. GUILBAULT #1144 -----QAS: M. GUILBAULT #1144 GOODYEAR PD Test g/210L Time -----Air Blank 0-000 10:52:01 Cal Check 0.101 10:52:20 Air Blank

operator's Signature