# EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A) $\,$

### ARIZONA DEPARTMENT OF PUBLIC SAFETY

# STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

## STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST, M. GUENBAUF 114 AGENCY GOODY EAR AS
DATE 9/27/2011 TIME (5-3/
INTOXILYZER SERIAL # 80-000312 LOCATION/07-01 S ESTATUA PRUY
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution AC.
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
<ol> <li>Intoxilyzer 8000 display reads "PUSH BUTTON TO START"</li> <li>Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.</li> </ol>
4. Air blank completed. 5. Calibration check completed. Test results 0. AC. 6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE 1144
DPS Form Exh G-2 (Rev 05-01)
(

Location: 10701 S ESTRELLA Serial Number: 80-000312 Core Version: 8105.48

09/27/2011

18:31:19

Standard Lot#: 06011100A1

Last Changed By: M. GUILBAULT #1144

-----

QAS: M. GUILBAULT #1144

GOODYEAR PD

-----

Operator: M. GUILBAULT #1144

GOODYEAR PD

Test	g/210L	Time
Air Blank	0.000	18:32:05
0.100 Cal Check	0.101/	18:32:25
Air Blank	0.000	18:32:55

Preventative Maintenance Performed -- Timer Reset

## EXHIBIT G-4 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

#### ARIZONA DEPARTMENT OF PUBLIC SAFETY

## STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST M. GUZINGUT AGENCY GOOJGEAN PDATE 9/27/2011 TIME 1823
DATE 9/27/2011 TIME 1833
INTOXILYZER SERIAL # 80-000312 LOCATION 10701 SESTIFLED PRO
1. Display Reads "PUSH BUTTON TO START"
DIAGNOSTIC TESTS  1. Clock time check.  2. Date check.
OPERATIONAL TESTS  1. Alcohol-free subject test result 0
Instrument is operating properly and accurately. YES NO
COMMENTS
SIGNATURE  DPS Form Fyb G 4 (Pay 05 01)

Location: 10701 S ESTRELLA Serial Number: 80-000312 Core Version: 8105.48

09/27/2011

(18:33:06)

Standard Lot#: 06011100A1

Last Changed By: M. GUILBAULT

#1144

QAS: M. GUILBAULT

#1144

GOODYEAR PD

Operator: M. GUILBAULT

#1144

GOODYEAR PD

Subject: TEST, TEST DOB: 01/01/1990

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

	Test	g/210L	Time
	Air Blank	0.000	18:33:51
	Diagnostic Test	Pass	18:34:26
	Air Blank	0.000	18:34:54
	0.100 Cal Check	0.101	18:35:15
	Air Blank	(0.000)	18:35:44
	Subject Test	0.000	18:35:56
	Air Blank	RFI*	18:36:07
	Air Blank	IPS**	18:36:17
200			
	*RFI Detect \	*	
(	**Improper Samp	e A	
	,	<b>V</b>	

Not a Successfully Completed Test Sequence

Location: 10701 S ESTRELLA Serial Number: 80-000312

Core Version: 8105.48

09/27/2011

18:36:22

Standard Lot#: 06011100A1

Last Changed By: M. GUILBAULT

#1144

QAS: M. GUILBAULT

GOODYEAR PD

#1144

Operator: M. GUILBAULT

#1144

GOODYEAR PD

Subject: TEST, TEST

DOB: 01/01/1990

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210h	Time
Air Blank	ABT*	18:36:47
Air Blank	(0.000)	18:37:15

<sup>\*</sup>Sequence Aborted

Location: 10701 S ESTRELLA Serial Number: 80-000312

Core Version: 8105.48

09/27/2011

18:37:20

Standard Lot#: 06011100A1

Last Changed By: M. GUILBAULT

#1144

QAS: M. GUILBAULT

#1144

GOODYEAR PD

Operator: M. GUILBAULT

#1144

GOODYEAR PD

Subject: TEST, TEST DOB: 01/01/1990

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	18:38:05
Diagnostic Test	Pass	18:38:40
Air Blank	0.000	18:39:07
0.100 Cal Check	0.101	18:39:28
Air Blank	0.000	18:39:58
Subject Test	0.073*)	18:43:06
Air Blank	0.000	18:43:38
Air Blank	0.000	18:44:05
Subject Test	XXX**/	18:44:31
Air Blank	0.000	18:45:04

\*Deficient Sample \*\*Invalid Sample

Begin new deprivation period

Not a Successfully Completed Test Sequence

# EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

## ARIZONA DEPARTMENT OF PUBLIC SAFETY

# STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

### STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M- GUTUNAUT AGENCY GOOD, END PA
DATE // 27/201/ TIME /845
INTOXILYZER SERIAL # 80-0003/2 LOCATION 670/ STSTATUS PK
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution (OR)
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
<ol> <li>Intoxilyzer 8000 display reads "PUSH BUTTON TO START"</li> <li>Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.</li> </ol>
4. Air blank completed. 5. Calibration check completed. Test results 0. / O AC. 6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE_
DPS Form Exh G-2 (Rev 05-01)

Location: 10701 S ESTRELLA Serial Number: 80-000312 Core Version: 8105.48

09/27/2011

18:45:16

Standard Lot#: 06011100A1

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

\_\_\_\_\_

Operator: M. GUILBAULT #1144

GOODYEAR PD

Test	g/210L	Time
Air Blank	0.000	18:45:45
0.100 Cal C	heck 0.101	18:46:06
Air Blank	0.000	18:46:36

Preventative Maintenance Performed -- Timer Reset