EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. GURUSSINT /14 AGENCY 6000 YEAR PO
TIME 7218
INTOXILYZER SERIAL# 80-001858 LOCATION [11 5 LETCHTEED R
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution AC. OR
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C 2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START" 3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER. 4. Air blank completed. 5. Calibration check completed. Test results 0AC. 6. Air blank completed. 7. Remove printed record. Attach the record to the completed checklist.

DPS Form Exh G-2 (Rev 05-01)

Location: 1111 S LITCHFIELD RD

Serial Number: 80-001858 Core Version: 8105.48

08/08/2013

22:18:25

Standard Lot#: 34011100A1

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

Operator: M. GUILBAULT #1144

GOODYEAR PD

Test	g/210L	Time
Air Blank	0,000	22:18:54
0.100 Cal Ch	eck 6.099	22:19:15
Air Blank	00000	22:19:45

Preventative Maintenance Performed -- Timer Reset

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. GURLMANIT AGENCY 6000 YEAR PD
DATE 8/15/13 TIME 2235
INTOXILYZER SERIAL# 80-00/858 LOCATION /// S GITCHEREIS B
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution AC
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
 Intoxilyzer 8000 display reads "PUSH BUTTON TO START" Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
4. Air blank completed. 5. Calibration check completed. Test results 0. 199 AC. 6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE // // //

DPS Form Exh G-2 (Rev 05-01)

Location: 1111 S LITCHFIELD RD

Serial Number: 80-001858 Core Version: 8105.48

08/15/2013

22:35:09

Standard Lot#: 34011100A1

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

Operator: M. GUILBAULT #1144

GOODYEAR PD

Test	g/210L	Time
~~~~~		
Air Blank	0,000	22:35:39
Air Blank 0.100 Cal Check	(0.099)	22:36:00
Air Blank	00000 ک	22:36:29

Preventative Maintenance Performed -- Timer Reset

### EXHIBIT G-4 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

#### ARIZONA DEPARTMENT OF PUBLIC SAFETY

## STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

#### STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST M. GUZUMA-IT /14 (AGENCY GODD YEAR P)
DATE 8/15/13 TIMB 2236
INTOXILYZER SERIAL# 80-00/858 LOCATION /// S LETCALEE-O Pa
( Display Reads "PUSH BUTTON TO START"
DIAGNOSTIC TESTS  (7) 1. Clock time check.  (9) 2. Date check.
OPERATIONAL TESTS  ( 1. Alcohol-free subject test result 0
COMMENTS
SIGNATURE 1/14
DPS Form Exh G-4 (Rev 05-01)

Location: 1111 S LITCHFIELD RD

Serial Number: 80-001858 Core Version: 8105.48

08/15/2013

22:36:37

Standard Lot#: 34011100A1

Last Changed By: M. GUILBAULT

#1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

Operator: M. GUILBAULT #1144

GOODYEAR PD

Subject: TEST, TEST DOB: 10/10/1990

Sex: M Weight: 190

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	22:37:21
Diagnostic Test	Pass	22:37:56
Air Blank	0.000	22:38:23
0.100 Cal Check	0.099	22:38:44
Air Blank	0.000	22:39:13
Subject Test -	0.000	22:39:30
Air Blank	IPS* )	22:39:37
Air Blank	RFI**	22:39:44
	and the second	

^{*}Improper Sample

#### Not a Successfully Completed Test Sequence

^{**}RFI Detect

Location: 1111 S LITCHFIELD RD

Serial Number: 80-001858 Core Version: 8105.48

08/15/2013

22:39:4

Standard Lot#: 34011100A1

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD #1144

Operator: M. GUILBAULT ·

#1144

GOODYEAR PD

Subject: TEST, TEST DOB: 10/10/1990

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	22:40:38
Diagnostic Test	Pass	22:41:13
Air Blank	0.000	22:41:40
0.100 Cal Check	0.099	22:42:01
Air Blank	0.000	22:42:31
Subject Test	0.048*	22:45:38
Air Blank	0.000	22:46:10
Air Blank	0.000	22:46:38
Subject Test	( XXX**)	22:47:01
Air Blank	0.000	22:47:34

^{*}Deficient Sample

Begin new deprivation period

^{**}Invalid Sample

Location: 1111 S LITCHFIELD RD

Serial Number: 80-001858 Core Version: 8105.48

08/15/2013

22:47:37

Standard Lot#: 34011100A1

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

Operator: M. GUILBAULT. #1144

GOODYEAR PD

Subject: TEST, TEST

DOB: 10/10/1990

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	22:48:25
Diagnostic Te	st Pass	22:49:00
Air Blank	0.000	22:49:28
Reference	ABT*	22:49:33
Air <u>Blank</u>	0.000	22:50:01

*Sequence Aborted

### EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

#### ARIZONA DEPARTMENT OF PUBLIC SAFETY

### STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

#### STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST M. GI ELMONT 1144 AGENCY 6001 YEAR PD
DATE \$1/5/13 TIME 2750
INTOXILYZER SERIAL # 90-001858 LOCATION /// S LZTCHEEUS A
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution AC.  OR.
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
<ol> <li>Intoxilyzer 8000 display reads "PUSH BUTTON TO START"</li> <li>Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.</li> </ol>
<ul> <li>4. Air blank completed.</li> <li>5. Calibration check completed. Test results 0. DGG AC.</li> <li>6. Air blank completed.</li> </ul>
7. Remove printed record. Attach the record to the completed checklist.  SIGNATURE

DPS Form Exh G-2 (Rev 05-01)

Location: 1111 S LITCHFIELD RD

Serial Number: 80-001858 Core Version: 8105.48

Standard Lot#: 34011100A1

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144 GOODYEAR PD

Operator: M. GUILBAULT #1144 GOODYEAR PD .

08/15/2013

~----

Test	g/210L	Time
Air Blank	9.008	22:50:43
0.100 Cal Chec Air Blank	k / 0.099	22:51:04
Air Blank	( 0.000/	22:51:34
	. /	

Preventative Maintenance Performed -- Timer Reset