### ARIZONA DEPARTMENT OF PUBLIC SAFETY

# STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

DATE (2/6/201) DATE (2/6/201)
DATE [4/6/201] TIME 1853
INTOXILYZER SERIAL # 80-00/858 LOCATION 190 N GTCHETELD RO
LOCATION /90 N CATCHETELD RI)  1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution OR  OR  AC.
Pour a standard alcohol concentration solution  AC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ±  2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START"  3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.  4. Air blank completed.  5. Calibration check completed. Test results 0. DS AC.  6. Air blank completed.  7. Remove printed record. Attach the record to the completed checklist.
DPS Form Exh G-2 (Rev 05-01)

INTOXILYZER 8000
Location: 190 N LITCHFIELD RD
Serial Number: 80-001858
Core Version: 8105.48
12/16/2011

Standard Lot#: 01011100A1
Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144
GOODYEAR PD

Operator: M. GUILBAULT #1144
GOODYEAR PD

Test

Test

g/210L

Time

Test	g/210L	Time	Q
Air Blank	0.000	18:5	54:11
0.100 Cal Cl	0.098		54:32
Air Blank	0.000		5:02

### ARIZONA DEPARTMENT OF PUBLIC SAFETY

# STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

QA SPECIALIST M. GUMAULT 1144 AGENCY GOOD YEAR M
DATE_ / M/F / /O//
INTOVIL WIED ON A CONTROL TIME 03/6
INTOXILYZER SERIAL # SO-00/858 LOCATION / 90 N LATCHFIELD RA
1. Ensure that gas tank is attached to instrument and contain
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution / WAC.
Pour a standard alcohol concentration solutionAC.  AC, into a clean dry simulator and assemble the 0.2°C  2. Intoxilyzer 8000 display reads **TRY ray as
2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START"  3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is  4. Air blank completed
4. Air blank completed.
5. Calibration check completed. Test results 0. / 00 AC.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE //YY
DPS Form Exh G-2 (Rev 05-01)

Location: 190 N LITCHFIELD RD

Serial Number: 80-001858 Core Version: 8105.48

12/17/2011

03:16:11

\_\_\_\_\_\_ Standard Lot#: 01011100A1

Last Changed By: M. GUILBAULT #1144 ------

QAS: M. GUILBAULT #1144

GOODYEAR PD

-----Operator: M. GUILBAULT #1144

GOODYEAR PD

Test	g/210L	Time
		TIME
Air Blank 0.100 Cal Check Air Blank	0.000	03:16:48 03:17:09 03:17:38

### ARIZONA DEPARTMENT OF PUBLIC SAFETY

# STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

QA SPECIALIST M. GUTLBAUT 1/44 AGENCY GOOD YEAR PD DATE 12/17/2011
DATE 12/17/2011
INTOXILYZER SERIAL # 80-00/858 LOCATION //// S LFTCHFIELD K
1. Ensure that gas tank is attached to instrument and an instrument and a second secon
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution  OR  Pour a standard alcohol concentration solution  AC, into a clean dry simulator and assemble the 0.2°C.
(Tw) 2. Interviewer 2000 # 1
2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START"  3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is  4. Air blank completed
4. Air blank completed. 5. Calibration check completed. Test results 0. / OO AC.  6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE
DPS Form Exh G-2 (Rev 05-01)

Location: 1111 S LITCHFIELD RD

Serial Number: 80-001858 Core Version: 8105.48

12/17/2011

03:18:17

Standard Lot#: 01011100A1

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

Onomatana

Operator: M. GUILBAULT #1144

GOODYEAR PD

Test	g/210L	Time
Air Blank	0.000	03:18:46
0.100 Cal Check	0.100	03:19:07
Air Blank	0.000	03:19:36

#### ARIZONA DEPARTMENT OF PUBLIC SAFETY

## STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

QA SPECIALIST M. GUELSAUG 194 AGENCY GODDYEAR PS.
DATE 10171 LDI
INTOXILYZER SERIAL # 80-00/858 LOCATION //// S LOCATION //// S LOCATION RD
( 6) 1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution ( 100 AC
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ±  (**) 2. Intoxilyzer 8000 display reads "DIGILID TEMPONETE and allow temperature to reach 34°C ±
made press ENTER.  After selection is
5. Calibration check completed. Test results 0. AC.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE
DPS Form Exh G-2 (Rev 05-01)

Location: 1111 S LITCHFIELD RD

Serial Number: 80-001858

Core Version: 8105.48

12/27/2011

19:01:05

Standard Lot#: 01011100A1

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

Operator: M. GUILBAULT #1144

GOODYEAR PD

Test	g/210L	Time
Air Blank 0.100 Cal Check Air Blank	0.000	19:01:38 19:01:59 19:02:28


#### ARIZONA DEPARTMENT OF PUBLIC SAFETY

## STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

#### STANDARD QUALITY ASSURANCE PROCEDURE

DATE /2/27/2011	AGENCY (	4 mary	TOP DA	
DATE /2/27/2011	TIME	P0059	902	
INTOXILYZER SERIAL# 80-00 1558	LOCATION	11115	(J.T. J.C. J. A	
1. Display Reads "PUSH BUTTON TO START"	2		THE CONTINUE	
DIAGNOSTIC TESTS 1. Clock time check. 2. Date check.			•	
OPERATIONAL TESTS  AC.  AC.  AC.  AC.  AC.  AC.  AC.  AC	printed AC. Result 0.	100	AC.	
COMMENTS				
		<del> </del>		
			·	
	2			
SIGNATURE				
DPS Form Exh G-4 (Rev 05-01)				

INTOXILYZER 8000 Location: 1111 S LITCHFIELD RD Serial Number: 80-001858 Core Version: 8105.48 12/27/2011



	17.02.30
Standard Lot#: 01011100A1	
Last Changed By: M. GUILBAUL	T #1144
QAS: M. GUILBAULT GOODYEAR PD	#1144
Operator: M. GUILBAULT GOODYEAR PD	#1144
Subject . TROT	

Subject: TEST, TEST DOB: 01/01/2000

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210T.	m :
Air Blank Diagnostic Test Air Blank 0.100 Cal Check Air Blank Subject Test Air Blank Air Blank	g/210L 0.000 Pass 0.000 0.100 0.000 1PS* RFI**	Time  19:03:23 19:03:58 19:04:26 19:04:46 19:05:16 19:05:36 19:05:36
*Improper Sample **RFI Detect	•	47.03.43

Not a Successfully Completed Test Sequence

INTOXILYZER 8000 Location: 1111 S LITCHFIELD RD Serial Number: 80-001858 Core Version: 8105.48 12/27/2011

19:05:48

Standard Lot#: 01011100A1
Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

Operator: M. GUILBAULT #1144 GOODYEAR PD

Subject: TEST, TEST DOB: 01/01/2000

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

Test

Air Blank

Air Blank

Air Blank

79:06:16

19:06:44

\*Sequence Aborted

Location: 1111 S LITCHFIELD RD

Serial Number: 80-001858

Core Version: 8105.48

12/27/2011

19:06:48

Standard Lot#: 01011100A1

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

Operator: M. GUILBAULT #1144

GOODYEAR PD

Subject: TEST, TEST DOB: 01/01/2000

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	19:07:33
Diagnostic Test	Pass	19:08:08
Air Blank	0.000	19:08:35
0.100 Cal Check	0.100	19:08:55
Air Blank	0.000	19:09:26
Subject Test	0.045*	19:12:33
Air Blank	0.000	19:13:04
Air Blank	0.000	19:13:32
Subject Test	( XXX** )	19:13:48
Air Blank	0.000	19:14:22

\*Deficient Sample \*\*Invalid Sample

Begin new deprivation period

Location: 1111 S LITCHFIELD RD

Serial Number: 80-001858

Core Version: 8105.48

12/27/2011

19:14:32

Standard Lot#: 01011100A1

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

Operator: M. GUILBAULT #1144

GOODYEAR PD

------

Test	g/210L	Time
Air Blank	0.000	19:15:01
0.100 Cal Check		19:15:22
Air Blank	0.000	19:15:52

#### ARIZONA DEPARTMENT OF PUBLIC SAFETY

### STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

QA SPECIALIST M. GUSUBAUT 1144 AGENCY GOODYEAR PA
DATE 12/17/2011 TIME 1914
INTOXILYZER SERIAL# 80-00 1858 LOCATION //// SLETCHFEELA RO
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution AC
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START"  3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
4. Air blank completed. 5. Calibration check completed. Test results 0. AC. 6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE
DPS Form Exh G-2 (Rev 05-01)