EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPE	ECIALIST M. LOUTIST SIT SIVY	AGENCY GOOGLEAN A		
DATE_	3/14/2013	TIME (7-0/		
XOTAI	CILYZER SERIAL# <u>\$6-001858</u>	LOCATION 10701 S ESTRELLA PKW-		
POT	Ensure that gas tank is attached to instrument and co	ontains a standard alcohol concentration solution AC.		
HERE E	Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C 2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START" 3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER. 4. Air blank completed. 5. Calibration check completed. Test results 0AC. 6. Air blank completed. 7. Remove printed record. Attach the record to the completed checklist.			

DPS Form Exh G-2 (Rev 05-01)

INTOXILYZER 8000

Location: 10701 S ESTRELLA Serial Number: 80-001858 Core Version: 8105.48

03/14/2013

17:01:47

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

••••

Operator: M. GUILBAULT #1144

GOODYEAR PD

Test g/210L Time

Air Blank 0.000 0.100 Cal Check 0.100

0.000 17:02:37 0.100 17:02:58

Air Blank 0,000

17:03:28

Preventative Maintenance Performed -- Timer Reset HA

INTOXILYZER 8000

Location: 1111 S LICHFIELD RD

Serial Number: 80-000312 Core Version: 8105.48

03/14/2013

_____ Standard Lot#: 13712100A2

Last Changed By: M. GUILBAULT #1144

QAS: M. GUILBAULT #1144

GOODYEAR PD

Operator: M. GUILBAULT #1144

GOODYEAR PD

Test	g/210L	Time
Air Blank 0.100 Cal Check	0.000	17:50:10 17:50:31
0.100 Cal Check Air Blank	0.000	17:51:01

Preventative Maintenance Performed -- Timer Reset