EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST TO ROGERS AGENCY GOODYEAR P.D.
DATE 5-21-07 TIME /12/
INTOXILYZER SERIAL # 80-001858 LOCATION GOODYEAR P.D.
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution . IDO AC
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START" 3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER.
4. Air blank completed. Calibration check completed. Test results 0. 100 AC.
6. Air blank completed 7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE #1/23
DPS Form Exh G-2 (Rev 05-01)

INTOXILYZER 8000

Location: GOODYEAR POLICE DEPT

Serial Number: 80-001858

05/21/2007

11:21:42

Standard Lot#: 536401I

Last Changed By: M. SLONEKER #6559

QAS: J. ROGERS #1123

GOODYEAR PD

Test	g/210L	Time
Air Blank	0.000	11:22:09
Cal Check	0.100	11:22:28
Air Blank	0.000	11:22:57

Operator's Signature