EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST T. ROGERS DATE 11-8-07	AGENCY GOODYEAR P.D.
DATE 11-8-07	TIME1536
INTOXILYZER SERIAL# 80 - 001858	LOCATION GOODY FAR P.D.
() 1. Ensure that gas tank is attached to instrument and o	contains a standard alcohol concentration solution .100 AC.
	AC, into a clean dry simulator and assemble the Turn on the simulator and allow temperature to reach $34^{\circ}C \pm$
2. Intoxilyzer 8000 display reads "PUSH BUTTON 7	TO START" dry control test or "W" for wet control test. After selection is
4. Air blank completed. 5. Calibration check completed. Fest results 0.	
7. Remove printed record. Attach the record to the consideration of the	ompleted checklist.
DPS Form Exh G-2 (Rev 05-01)	

INTOXILYZER 8000

Location: GOODYEAR POLICE DEPT

Serial Number: 80-001858

11/08/2007

15:36:59

Standard Lot#: 706502I

Last Changed By: W. WILL #974

QAS: J. ROGERS #1123

GOODYEAR PD

Test g/210L Time -----

Air Blank Cal Check

0 000 5 0.099 0.000

) 15:37:26 15:37:45 15:38:14

Air Blank

Operator's \$ignature