$EXHIBIT~G-4 \\ THIS REPORT PREPARED PURSUANT~TO~DUTY~IMPOSED~BY~A.A.C.~R13-10-104~(A) \\$

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD QUALITY ASSURANCE PROCEDURE

| QA SPECIALIST K. MIYAZAN 1139 AGENCY GODDYGAR PD |
|--|
| DATE 5 (30/2) TIME 2115 |
| INTOXILYZER SERIAL # 80-001858 LOCATION 11 N 145 714 ANS |
| (V) 1. Display Reads "PUSH BUTTON TO START" |
| DIACNOSTIC TESTS (') 1. Clock time check. () 2. Date check. |
| OPERATIONAL TESTS (1) 1. Alcohol-free subject test result 0 |
| |
| |
| SIGNATURE 139 |

DPS Form Exh G-4 (Rev 05-01)

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

05/30/2021 21:15:37

Standard Lot#: 2722000A1

Last Changed By: K. MIYAZATO #1139

QAS: K. MIYAZATO #1139

GOODYEAR PD

Operator: K. MIYAZATO #1139

GOODYEAR

Subject: SQAP, TEST DOB: 04/02/1973

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

| Test | g/210L | Time |
|-----------------|--------|----------|
| Air Blank | 0.000 | 21:17:26 |
| Diagnostic Test | Pass | 21:18:01 |
| Air Blank | 0.000 | 21:18:28 |
| 0.100 Cal Check | 0.100 | 21:18:49 |
| Air Blank | 0.000 | 21:19:19 |
| Subject Test | 0.000 | 21:19:35 |
| Air Blank | ABT* | 21:19:43 |
| Air Blank | 0.000 | 21:20:12 |

^{*}Sequence Aborted

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

05/30/2021 21:20:16

Standard Lot#: 2722000A1

Last Changed By: K. MIYAZATO #1139

QAS: K. MIYAZATO #1139

GOODYEAR PD

Operator: K. MIYAZATO #1139

GOODYEAR PD

Subject: SQAP, TEST DOB: 04/02/1973

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

 Test
 g/210L
 Time

 Air Blank
 IPS*
 21:21:13

 Air Blank
 0.000
 21:21:41

^{*}Improper Sample

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

05/30/2021

21:21:45

Standard Lot#: 2722000A1

Last Changed By: K. MIYAZATO #1139

QAS: K. MIYAZATO #1139

GOODYEAR PD

Operator: K. MIYAZATO #1139

GOODYEAR PD

Subject: SQAP, TEST DOB: 04/02/1973

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

| Test | g/210L | Time | |
|-----------|--------|----------|--|
| Air Blank | RFI* | 21:22:33 | |
| Air Blank | 0.000 | 21:23:01 | |

^{*}RFI Detect

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

05/30/2021 21:23:06

Standard Lot#: 2722000A1

Last Changed By: K. MIYAZATO #1139

QAS: K. MIYAZATO #1139

GOODYEAR PD

Operator: K. MIYAZATO #1139

GOODYEAR PD

Subject: SQAP, TEST DOB: 04/02/1973

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

| Test | g/210L | Time |
|-----------------|--------|----------|
| Air Blank | 0.000 | 21:24:03 |
| Diagnostic Test | Pass | 21:24:38 |
| Air Blank | 0.000 | 21:25:05 |
| 0.100 Cal Check | 0.100 | 21:25:26 |
| Air Blank | 0.000 | 21:25:55 |
| Subject Test | 0.063* | 21:29:03 |
| Air Blank | 0.000 | 21:29:35 |
| Air Blank | 0.000 | 21:30:03 |
| Subject Test | XXX** | 21:30:17 |
| Air Blank | 0.000 | 21:30:50 |

^{*}Deficient Sample

Begin new deprivation period

^{**}Invalid Sample

Location: 11 N 145TH AVE Serial Number: 80-001858 Core Version: 8105.48

05/30/2021 21:31:17

Standard Lot#: 2722000A1

Last Changed By: K. MIYAZATO #1139

QAS: K. MIYAZATO #1139

GOODYEAR PD

Operator: K. MIYAZATO #1139

GOODYEAR PD

| Test | g/210L | Time |
|-----------------|--------|----------|
| | | |
| Air Blank | 0.000 | 21:31:47 |
| 0.100 Cal Check | 0.100 | 21:32:08 |
| Air Blank | 0.000 | 21:32:38 |

Preventative Maintenance Performed -- Timer Reset

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

| QA SPECIALIST K M YAZATU 139 AGENCY GOUNGERE PA |
|--|
| DATE $\frac{30}{30}$ TIME $\frac{2131}{30}$ |
| INTOXILYZER SERIAL# 80-00/858 LOCATION // N 1457H AVE |
| 1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution AC. |
| Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C |
| Intoxilyzer 8000 display reads "PUSH BUTTON TO START" Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is made press ENTER. Air blank completed. |
| () 5. Calibration check completed. Test results 0. O AC. () 6. Air blank completed. |
| 7. Remove printed record. Attach the record to the completed checklist. |
| SIGNATURE /139 |
| DPS Form Exh G-2 (Rev 05-01) |



7 Eastgate Dr. • P.O. Box 790 • Jacksonville, IL 62651-0790 217-245-2183 • Fax: 217-243-7634 • www.ilmoproducts.com

Certificate of Analysis

Certificate ID:

13377

Part #:

BAC105L100T

Cylinder Size:

105L

Lot Number:

27220100A1

Expiration:

12/5/2022

(). | ()() BAC (For the calibration of instruments used to determine breath alcohol concentration)

Contents:

105 Liters @ 1000 psig 70°F (21°C)

Analytical

Reported

Accuracy

Analytical

Component:

Concentration:

(U, k=2):

Method:

Ethanol Nitrogen 260 ppm Balance +/-0.002 BAC(G/310L) NDIR

[5.2 ppm]

Distributed by:

CMI Inc.

316 East Ninth Street Owensboro, KY 42303 Phone 866-835-0690 www.alcoholtest.com

*Traceable to:

Certified Reference Material - 262.4 µmol/mol

Ethanol in Nitrogen - Serial No. GN0015026 Lot No. 050319E11

Store in dry area, away from sources of heat, ignition and direct sunlight. Do not allow storage area to exceed 52 °C (125 °F).

Specialty Gas Lab Tech

Accreditation #61895

The calibration results within this certificate were obtained using equipment and standards capable of producing analytical results traceable to NIST, and apply only to the items contained on this certificate. ILMO Products Company makes no warranty or representation as to the suitability of the use of any information provided for any particular purpose. The information use is at the sole discretion and risk of the user. Liability shall be limited to established replacement cost of this material or service.



Safety Data Sheet

Ethanol in Nitrogen

www.ilmoproducts.com

Section 1: Product and Company Identification

ILMO Products Company 7 Eastgate Drive, Jacksonville, Illinois 62650 217-245-2183 800-424-9300 (Chemtrec)

Fax 217-243-7634 E-mail: info@ilmoproducts.com Web: www.ilmoproducts.com

Product Code: Ethanol in Nitrogen Part Number: BAC

Section 2: Hazards Identification



Hazard Classification: Gases Under Pressure

Hazard Statements: Contains gas under pressure; may explode if heated

Precautionary Statements

Storage: Protect from sunlight. Store in well-ventilated place.

Section 3: Composition/Information on Ingredients

| | CAS# | Concentration |
|----------|-----------|---------------|
| Ethanol | 64-17-5 | 5-500 ppm |
| Nitrogen | 7727-37-9 | Balance |

ILMO Products Company. Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved

page 1 of 6 Generated: 02/08/2017 10:18:45

| | Methods for Cleanup | |
|----------|---|-----|
| | Small spills: Absorb with sand or other noncombustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal. | |
| Nitrogen | N/A | N/A |

Section 7: Handling and Storage

| | Handling | Storage | |
|---|---|--|--|
| Ethanol Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 125°F (52°C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods. | | Do not get liquid in eyes, on skin, or clothing. Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Open valve slow! Close cylinder valve after each use; keep closed even whe empty. If valve is hard to open, discontinue use and contar your supplier. | |
| Nitrogen | Store and handle in accordance with all current regulations and standards. Subject to storage regulations; U.S. OSHA 29 CFR | Keep separated from incompatible substances. | |

Section 8: Exposure Controls/Personal Protection

| | Exposure Guidelines |
|----------|--|
| Ethanol | ETHYL ALCOHOL, 100%: ETHYL ALCOHOL (ETHANOL): 1000 ppm (1900 mg/m3) OSHA TWA 1000 ppm ACGIH TWA 1000 ppm (1900 mg/m3) NIOSH recommended TWA 10 hour(s) |
| Nitrogen | NITROGEN COMPRESSED GAS: NITROGEN: ACGIH (simple asphyviant) |

Engineering Controls

| | Eye Protection | Skin Protection | Respiratory Protection |
|----------|--|---|---|
| Ethanol | Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. | Wear appropriate chemical resistant clothing. | Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive- pressure mode in combination with a separate escape supply. |
| Nitrogen | Eye protection not required, but recommended. | Protective clothing is not required. | Respiratory protection may be needed for frequent or heavy exposure. |

- General Hygiene considerations

 Avoid breathing vapor or mist

 Avoid contact with eyes and skin

 Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

| | Physical State | Appearance | Color | Change in Appearance | Physical Form | Odor | Taste |
|----------|----------------|------------|-----------|----------------------|-----------------|---------------|---------------|
| Ethanol | Liquid | Clear | Coloriess | N/A | Volatile liquid | Pleasant odor | Burning taste |
| Nitrogen | Gas | Clear | Colorless | N/A | Gas | Odoriess | Tasteless |

| | Flash Po | int | Flammability | Partition Coefficien | | utoignition emperature | | Upper Explosiv Limits | e Lower Limits | Explosive |
|----------|------------------|---------|-------------------|-------------------------|---------------------|---------------------------|----|--------------------------|---------------------|-----------|
| Ethanol | 55 F (13 (CC) | 2) | IB | Not availab | le 6 | 85 F (363 C) | | 0.19 | 0.033 | |
| Nitrogen | Not flamn | nable | Not available | Not availab | le N | Ionflammable | | Nonflammable | Nonflar | nmable |
| | Boiling Point | Freezin | yapor Pressure | Vapor Density | Specific Gravity | Water Solubility | pН | Odor Threshold | Evaporation Rate | Viscosity |

| | Chemical Substance | Chemical Family | Trade Names |
|----------|-------------------------|--|--|
| Ethanol | ETHYL ALCOHOL. 100% | hydroxyls, aliphatic, alcohols, aliphatic | ETHANOL; ETHYL ALCOHOL; A. ALCOHOL: ALCOHOL ANHYDROUS, ALGRAIN; ANHYDROL; Absolute aicohol; Anhydrous ethanol; Ethanol denatured; Fermentation alcohol; Grain aicohol; 1-Hydroxyethane; Methyl carbinol; Ethyl alcohol anhydrous; Absolute ethanol; Denatured ethanol; ETHYL HYDRATE; ETHYL HYDROXIDE; JAYSOL; TECSOL; STCC 4909159; UN 170; C2HBO |
| Nitrogen | NITROGEN, COMPRESSED | Inorganic gases | DIATOMIC NITROGEN, DINITROGEN, NITROGEN-14; NITROGEN GAS; UN 1066; N2 |

Section 4: First Aid Measures

| -115 | Skin Contact | Eye Contact | Ingestion | Inhalation | Note to Physicians |
|----------|--|--|---|---|--|
| Ethanol | Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse. | Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention. | Contact local poison control center or physician immediately. Never make an unconscious person vomit or drink fluids. When vomiting occurs, keep head lower than hips to help prevent aspiration. If person is unconscious, turn head to side. Get medical attention immediately. | If adverse effects occur, remove to unconfaminated area. Give artificial respiration if not breathing. Get immediate medical attention. | For ingestion, consider gastric lavage. |
| Nitrogen | Wash exposed skin with soap and water. | Flush eyes with plenty of water. | If a large amount is swallowed, get medical attention. | If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical aftention. | For inhalation, consider oxygen. |

Section 5: Fire Fighting Measures

| | Suitable Extinguishing Media | Products of Combustion | Protection of Firefighters | | | |
|----------|--|---|--|--|--|--|
| Ethanol | Alcohol resistant foam, carbon dioxide, regular dry chemical, water, alcohol resistant foam Large fires. Use alcohol-resistant foam or flood with fine water spray. | Carbon monoxide, carbon dioxide, and toxic and irritating furnes | Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supplied. Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. | | | |
| Nitrogen | Non-flammable. Use suitable extinguishing media for surrounding fire. Cylinders may rupture or explode if exposed to heat. | Non-flammable | Respiratory protection may be needed for frequent or heavy exposure. | | | |

Section 6: Accidental Release Measures

| | Personal Precautions | Environmental Precautions | Methods for Containment |
|----------|--|---|--|
| Ethanol | Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. | Avoid heat, flames, sparks and other sources of ignition. | Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition. |
| Nitrogen | Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas. | No significant effects from contamination expected. | Stop leak if possible without personal risk. |

ILMO Products Company Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved

page 2 of 6 Generated: 02/08/2017 10:18:45

| | Boiling Point | Freezing Point | Vapor Pressure | Vapor Density | Specific Gravity | Water Solubility | pH | Odor Threshold | Evaporation Rate | Viscosity |
|----------|------------------|---------------------|-------------------------|------------------|---------------------|---------------------|-------------------|-------------------|---------------------------------|--|
| Ethanol | 172 F (78 C) | -179 F (- 117 C) | 40 mmHg @ 19 C | 1.59 (Air=1) | 0.7893 | Soluble | Not available | 5-10 ppm | 1.4 (carbon tetrachloride=1) | 1.17 mPa.s (1.17 centipoises @ 20 C; 1.074 mPa.s (1.074 centipoises @ 25 C |
| Nitrogen | -321 F (-196 | -346 F (- 210 C) | 760 mmHg @ -196 C | 0.967 (Air=1) | Not applicable | 1.6% @ 20 C | Not applicable | Not available | Not applicable | 0.01787 cP @ 27 C |

| | Molecular Weight | Molecular Formula | Density | Weight per Gallon | Volatility by Volume | Volatility | Solvent Solubility |
|----------|---------------------|----------------------|------------------|----------------------|-------------------------|------------|---|
| Ethanol | 46.07 | C-H3-C-H2-O- H | Not available | Not available | Not available | 1 | Soluble: Benzene, ether, acetone, chloroform, methanol, organic solvents |
| Nitrogen | 28.0134 | N2 | 1.2506 g/L | Not available | 100% | 1 | Soluble: Liquid ammonia |

Section 10: Stability and Reactivity

| | Stability | Conditions to Avoid | Incompatible Materials |
|----------|--|--|--|
| Ethanol | Stable at normal temperatures and pressure. | Stable at normal temperatures and pressure. | Halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases, combustible materials |
| Nitrogen | Stable at normal temperatures and pressure. | Stable at normal temperatures and pressure. | Metals, oxidizing materials |

| | Hazardous Decomposition Products | Possibility of Hazardous Reactions |
|----------|----------------------------------|------------------------------------|
| Ethanol | Oxides of carbon | Will not polymerize. |
| Nitrogen | Oxides of nitrogen | Will not polymerize |

Section 11: Toxicology Information

Acute Effects

| | Oral LD50 | Dermal LD50 | Inhalation |
|----------|---------------------------|---|---|
| Ethanol | 7 gm/kg oral- rat LD50 | LD50 (dermal, rabbit): greater than 15800 mg/kg (cited as greater than 20 mL/kg); at 20 mL/kg, 1/4 rabbits died | irritation, difficulty breathing, headache, drowsiness, symptoms of drunkenness |
| Nitrogen | Not available | Not available | Nausea, vomiting, difficulty breathing, headache, drowsiness, dizziness, tingling sensation, loss of coordination, convulsions coma |

| | Eye Irritation | Skin itritation | Serisitization |
|---------|--|--|--|
| Ethanol | Irritation, tearing | | Respiratory tract irritation, skin irritation, eye irritation, liver damage, central nervous system depression |
| | Contact with rapidly expanding gas may cause burns or frostbite | No information on significant adverse effects | Difficulty breathing |

Chronic Effects

| V-11/15 | Carcinogenicity | Mutagenicity | Reproductive Effects | Developmental Effects |
|----------|---|---------------|-------------------------|--------------------------|
| Ethanol | NTP: Known Human Carcinogen (Alcoholic beverages); IARC: Human Sufficient Evidence, Group 1 (Alcoholic beverages), Animal Inadequate Evidence; ACGIH: A4-Not Classifiable as a Human Carcinogen | Available | Available. | No data |
| Nitrogen | Not hazardous | Not available | Not available | No data |