EXHIBIT G-4 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD QUALITY ASSURANCE PROCEDURE

QA SPECIALIST KMIYAZATO 1139 AGENCY GOODY ZAR
DATE 4/27/2020 TIME 0354
INTOXILYZER SERIAL # 80-000312 LOCATION // N 145 TH AVE
1. Display Reads "PUSH BUTTON TO START"
DIAGNOSTIC TESTS () 1 Clock time check. () 2. Date check.
OPERATIONAL TESTS () A. Alcohol-free subject test result 0
COMMENTS
SIGNATURE (139
DPS Form Exh G-4 (Rev 05-01)

Location: 11 N 145TH AVE Serial Number: 80-000312 Core Version: 8105.48

04/27/2022

03:54:51

Standard Lot#: 27220100A1 Last Changed By: K. MIYAZATO	#1139
QAS: K. MIYAZATO GOODYEAR PD	#1139
Operator: K. MIYAZATO GOODYEAR PD	#1139

Subject: SQAP, TEST DOB: 04/02/1973

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	03:55:48
Diagnostic Test	Pass	03:56:23
Air Blank	0.000	03:56:51
0.100 Cal Check	0.099	03:57:11
Air Blank	0.000	03:57:41
Subject Test	0.000	03:57:55
Air Blank	ABT*	03:58:04
Air Blank	0.000	03:58:32

^{*}Sequence Aborted

Location: 11 N 145TH AVE Serial Number: 80-000312 Core Version: 8105.48

04/27/2022

03:58:36

Standard Lot#: 27220100A1 Last Changed By: K. MIYAZATO	#1139
QAS: K. MIYAZATO GOODYEAR PD	#1139
Operator: K. MIYAZATO GOODYEAR PD	#1139
CONTRACTOR OF THE CONTRACTOR O	

Subject: SQAP, TEST DOB: 04/02/1973

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	IPS*	03:59:12
Air Blank	0.000	03:59:41

^{*}Improper Sample

Location: 11 N 145TH AVE Serial Number: 80-000312 Core Version: 8105.48

04/27/2022

03:59:44

Standard Lot#: 27220100A1	
Last Changed By: K. MIYAZATO	#1139
QAS: K. MIYAZATO GOODYEAR PD	#1139
Operator: K. MIYAZATO GOODYEAR PD	#1139

Subject: SQAP, TEST DOB: 04/02/1973

Sex: M

Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	RFI*	04:00:20
Air Blank	0.000	04:00:49

^{*}RFI Detect

Location: 11 N 145TH AVE Serial Number: 80-000312 Core Version: 8105.48

04/27/2022 04:00:55

Standard Lot#: 27220100A1
Last Changed By: K. MIYAZATO #1139

QAS: K. MIYAZATO #1139

GOODYEAR PD

Operator: K. MIYAZATO #1139

GOODYEAR PD

Subject: SQAP, TEST DOB: 04/02/1973

Sex: M Weight: 200

15 Minute Deprivation Period? Yes

Test	g/210L	Time
Air Blank	0.000	04:01:47
Diagnostic Test	Pass	04:02:22
Air Blank	0.000	04:02:49
0.100 Cal Check	0.099	04:03:10
Air Blank	0.000	04:03:40
Subject Test	0.070*	04:06:47
Air Blank	0.000	04:07:19
Air Blank	0.000	04:07:46
Subject Test	XXX**	04:07:59
Air Blank	0.000	04:08:32

^{*}Deficient Sample

Begin new deprivation period

Not a Successfully Completed Test Sequence

^{**}Invalid Sample

EXHIBIT G-2 THIS REPORT PREPARED PURSUANT TO DUTY IMPOSED BY A.A.C. R13-10-104 (A)

ARIZONA DEPARTMENT OF PUBLIC SAFETY

STANDARD QUALITY ASSURANCE PROCEDURES INTOXILYZER MODEL 8000

STANDARD CALIBRATION CHECK PROCEDURE

QA SPECIALIST K MIYAZATO 139 AGENCY GOUDY SAR
DATE 4/27/2022 TIME
INTOXILYZER SERIAL# 80-808312 LOCATION // N 145 TH ME
1. Ensure that gas tank is attached to instrument and contains a standard alcohol concentration solution ACOR
Pour a standard alcohol concentration solutionAC, into a clean dry simulator and assemble the
simulator. Ensure that a tight seal has been made. Turn on the simulator and allow temperature to reach 34°C ± 0.2°C
() 2. Intoxilyzer 8000 display reads "PUSH BUTTON TO START"
3. Go to the "Control Testing Menu". Select "D" for dry control test or "W" for wet control test. After selection is
made press ENTER.
() A. Air blank completed. () S. Calibration check completed. Test results 0. 6 8 AC.
() 6. Air blank completed.
7. Remove printed record. Attach the record to the completed checklist.
SIGNATURE (39
PPS Form Exh G-2 (Rev 05-01)

Location: 11 N 145TH AVE Serial Number: 80-000312 Core Version: 8105.48

04/27/2022

04:08:49

Standard Lot#: 27220100A1

Last Changed By: K. MIYAZATO #1139

QAS: K. MIYAZATO #1139

GOODYEAR PD

Operator: K. MIYAZATO #1139

GOODYEAR PD

Test	g/210L	Time
Air Blank	0.000	04:09:23
0.100 Cal Check	0.098	04:09:43
Air Blank	0.000	04:10:13

Preventative Maintenance Performed -- Timer Reset

Location: 11 N 145TH AVE Serial Number: 80-000312 Core Version: 8105.48

04/27/2022

04:13:45

Standard Lot#: 28021100A1

Last Changed By: K. MIYAZATO #1139

QAS: K. MIYAZATO #1139

GOODYEAR PD

Operator: K. MIYAZATO #1139

GOODYEAR PD

Test	g/210L	Time
Air Blank	0.000	04:14:16
0.100 Cal Check	0.100	04:14:37
Air Blank	0.000	04:15:07

Preventative Maintenance Performed -- Timer Reset



7 Eastgate Dr. • P.O. Box 790 • Jacksonville, IL 62651-0790 217-245-2183 • Fax: 217-243-7634 • www.ilmoproducts.com

Certificate of Analysis

Certificate ID:

14350

Part #:

BAC105L100T

Cylinder Size:

105L

Lot Number:

28021100A1

Expiration:

12/5/2023

0.100 BAC (For the calibration of instruments used to determine breath alcohol concentration)

Contents:

105 Liters @ 1000 psig 70°F (21°C)

Analytical

Reported

Accuracy

Analytical

Component:

Concentration:

(U, k=2):

Method:

Ethanol Nitrogen

260 ppm Balance +/-0.002 BAC(G/210L) NDIR

[5.2 ppm]

d: Distributed by:

CMI Inc.

316 East Ninth Street Owensboro, KY 42303 Phone 866-835-0690 www.alcoholtest.com

*Traceable to:

Certified Reference Material - 262.4 µmol/mol

Ethanol in Nitrogen - Serial No. GN0015026 Lot No. 050319E11

Store in dry area, away from sources of heat, ignition and direct sunlight. Do not allow storage area to exceed 52 °C (125 °F).

Specialty/Gas Lab Tech

Issuance Date

PJLA
Calibration and Testing
Accreditation #61895

The calibration results within this certificate were obtained using equipment and standards capable of producing analytical results traceable to NIST, and apply only to the items contained on this certificate. ILMO Products Company makes no warranty or representation as to the suitability of the use of any information provided for any particular purpose. The information use is at the sole discretion and risk of the user. Liability shall be limited to established replacement cost of this material or service.



Safety Data Sheet

Ethanol in Nitrogen

www.ilmoproducts.com

Section 1: Product and Company Identification

ILMO Products Company 7 Eastgate Drive, Jacksonville, Illinois 62650 217-245-2183 800-424-9300 (Chemtrec)

Product Code: Ethanol in Nitrogen

Section 2: Hazards Identification



Hazard Classification: Gases Under Pressure

Hazard Statements: Contains gas under pressure; may explode if heated

Precautionary Statements

Storage: Protect from sunlight. Store in well-ventilated place.

Section 3: Composition/Information on Ingredients

	CAS#	Concentration
Ethanol	64-17-5	5-500 ppm
Nitrogen	7727-37-9	Balance

ILMO Products Company Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved

page 1 of 6 Generated: 02/08/2017 10.18:45

	Methods for Cleanup	Other Information
Ethanol	Small spills: Absorb with sand or other noncombustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal.	Not available
Nitrogen	N/A	N/A

Section 7: Handling and Storage

	Handling	Storage
Ethanol	Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Serve valve protection cap firmly in place by hand. Store only where temperature will not exceed 125°F (52°C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long penods.	Do not get liquid in eyas, on skin, or clothing. Protect cylinders from dampe. Use a suitable hand truck to move cylinders; do not drag, roll, slidid, or drop. Open valve slowly Close cylinder valve after each use; keep closed even wher empty. If valve is hard to open, disconlinue use and contact your supplier.
Nitrogen	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101	Keep separated from incompatible substances.

Section 8: Exposure Controls/Personal Protection

	Exposure Guidelines
Ethanol	ETHYL ALCOHOL, 100%: ETHYL ALCOHOL (ETHANOL): 1000 ppm (1900 mg/m3) OSHA TWA 1000 ppm ACGIH TWA 1000 ppm (1900 mg/m3) NIOSH recommended TWA 10 hour(s)
Nitrogen	NITROGEN, COMPRESSED GAS: NITROGEN: ACGIH (simple asphyxiant)

Engineering Controls

	Eye Protection	Skin Protection	Respiratory Protection
Ethanol	Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.	Wear appropriate chemical resistant clothing.	Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive- pressure mode in combination with a separate escape supply.
Nitrogen	Eye protection not required, but recommended.	Protective clothing is not required.	Respiratory protection may be needed for frequent or heavy exposure.

- General Hygiene considerations

 Avoid breathing vapor or mist

 Avoid contact with eyes and skin

 Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste Burning taste	
Ethanol	Liquid	Clear	Colorless	N/A	Volatile liquid	Pleasant odor		
Nitrogen	Gas	Clear	Colortess	N/A	Gas	Odorless	Tasteless	
	Flash Point	Flammability	Partition					
	riasii roint	riammasinty	Coefficie			er Explosive its	Lower Explos	
Ethanol	55 F (13 C) (CC)	IB		nt Temperatur	Lim	its		

	Boiling	Freez	ing Vapor	Vapor	Specific	Water	pH	Odor	Evaporation	Viscosity
Nitrogen	Not flame	nable	Not available	Not availab	le	Nonflammable		Nonflammable	Nonfla	mmable
Ethanol	55 F (13 (CC)	C)	IB	Not availab	le	685 F (363 C)		0.19	0.033	

- 15	Chemical Substance	Chemical Family	Trade Names
Ethanol	ETHYL ALCOHOL, 100%	hydroxyls, aliphatic, alcohols, aliphatic	ETHANDI; ETHYL ALCOHOL; Af, ALCOHOL; ALCOHOL ANHYDROUS; ALGRAIN: ANHYDROL Absolute aicohol; Arhydrous ethanol; Ethanol denatured; Fermentation aicohol; Grain aicohol; 1-hydrovyethane; Methyl carbinol; Ethyl aicohol anhydrous; Absolute ethanol; Denatured ethanol; ETHYL HYDRATE; ETHYL HYDROXIDE; JAYSOL; TECSOL; STCC 4999159; UN 1170; C21HBO
Nitrogen	NITROGEN, COMPRESSED GAS	Inorganic gases	DIATOMIC NITROGEN; DINITROGEN; NITROGEN; NITROGEN-14; NITROGEN GAS; UN 1066; N2

Section 4: First Aid Measures

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians	
Ethanol	Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.	Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Contact local poison control center or physician immediately. Never make an unconscious person vomit or drink fluids. When vomiting occurs, keep had lower than hips to help prevent aspiration. If person is unconscious, turn head to side. Get medical attention immediately.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. Get immediate medical attention.	For ingestion consider gastric lavege.	
Nitrogen Wash exposed skin with soap and water.		Flush eyes with plenty of water.	If a large amount is swallowed, get medical attention.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Gel immediate medical attention.	For inhalation, consider oxygen.	

Section 5: Fire Fighting Measures

	Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Ethanol	Alcohol resistant foam, carbon dioxide, regular dry chemical, water, alcohol resistant foam Large fires: Use alcohol-resistant foam or flood with fine water spray.	Carbon monoxide, carbon dioxide, and toxic and irritating turnes	 Any supplied-air respirator with full face-pose and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any supplied-air respirator with full face-posi- and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supplied.
Nitrogen	Non-flammable, Use suitable extinguishing media for surrounding fire, Cylinders may rupture or explode if exposed to heat.	Non-flammable	 Respiratory protection may be needed for frequent or heavy exposure.

Section 6: Accidental Release Measures

	Personal Precautions	Environmental Precautions	Methods for Containment
Ethanol	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	Avoid heat, flames, sparks and other sources of ignition.	Stop leak if possible without personal risk. Reduce vapors with water spray. Remove sources of ignition.
Nitrogen	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	No significant effects from contamination expected.	Stop leak if possible without personal risk.

ILMO Products Company Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved

page 2 of 8 Generated: 02/08/2017 10:18:45

	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	рН	Odor Threshold	Evaporation Rate	Viscosity
Ethanol	172 F (78 C)	-179 F (- 117 C)	40 mmHg @ 19 C	1.59 (Air=1)	0.7693	Soluble	Not available	5-10 ppm	1.4 (carbon letrachloride=1)	1.17 mPa.s (1.17 centipoises) @ 20 C; 1.074 mPa.s (1.074 centipoises @ 25 C
Nitrogen	-321 F (-196 C)	-346 F (- 210 G)	760 mmHg @ -196 C	0.967 (Air=1)	Not applicable	1.6% @ 20 C	Not applicable	Not available	Not applicable	0.01787 cP @ 27 C

	Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volume Volume	Volatility	Solvent Solubility
Ethanol	46.07	C-H3-C-H2-O- H	Not available	Not available	Not available	1	Soluble: Benzene, ether, acetone, chloroform, methanol, organic solvents
Nitrogen	28.0134	N2	1.2506 g/L	Not available	100%	1	Soluble: Liquid ammonia

Section 10: Stability and Reactivity

	Stability	Conditions to Avoid	Incompatible Materials
	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases, combustible materials
Nitrogen	Stable at normal temperatures and pressure.	Stable at normal temperatures and pressure.	Metals, oxidizing materials

	Hazardous Decomposition Products	Possibility of Hazardous Reactions Will not polymerize.		
Ethanol	Oxides of carbon			
Nitrogen	Oxides of nitrogen	Will not polymerize.		

Section 11: Toxicology Information

	Oral LD50 Dermal LD50		Inhalation		
Ethanol	7 gm/kg oral- rat LD50	LD50 (dermal, rabbit): greater than 15800 mg/kg (cited as greater than 20 mL/kg); at 20 mL/kg, 1/4 rabbits died	Irritation, difficulty breathing, headache, drowsiness, symptoms of drunkenness		
Nitrogen	Not available	Not available	Nausea, vomiting, difficulty breathing, headache, drowsiness, dizziness, tingling sensation, loss of coordination, convulsions coma		

	Eye Irritation	Skin Irritation	Sensitization		
Ethanol	Irritation, tearing		Respiratory tract irritation, skin irritation, eye irritation, liver damage, central nervous system depression		
Nitrogen	Contact with rapidly expanding gas may cause burns or frostbite	No information on significant adverse effects	Difficulty breathing		

Chronic Effects

	Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Ethanol	NTP: Known Human Carcinogen (Alcoholic beverages); IARC: Human Sufficient Evidence, Group 1 (Alcoholic beverages), Animal Inadequate Evidence, ACGIH: A4-Not Classifiable as a Human Carcinogen	Available.	Available.	No data
Nitrogen	Not hazardnus	Not available	Not available	No data